

Plug & Play Vehicle GPS Tracker











Plug & play

This tracker with OBD ${\rm I\hspace{-.1em}I}$ connector is aimed to achieve fast and easy installation.

Disconnect alert

An alert will be generated when the device is removed from the OBD connector.

Regular maintenance

Ensure the safety, reliability, drivability, comfort and longevity of a car.

Multiple alerts & reports

Support speeding/SOS/geo-fence alert, ACC ON & OFF/mileage/cornering report etc.

APPLICATION



Private car



Taxi



Truck

SPECIFICATIONS

| ITEM | SPECIFICATIONS |
|---------------------------|--|
| Dimension | 69.8 mm x 51.8 mm x 31.8 mm |
| Weight | 60g |
| Power supply | DC 12 V/24V 1A |
| Backup battery (optional) | 170 mAh/3.7 V (24 hours in power-saving mode; 1.5 hours in normal mode) |
| Power consumption | Current in standby mode: 68 mA |
| Operating temperature | -20°C to 55°C |
| Operating humidity | 5% to 95% |
| LED indicator | 2 indicators showing GSM and GPS status |
| Button/Switch | 1 SOS button 1 power button |
| Memory | 8 MB buffer |
| Sensor | 3-axis accelerometer |
| GSM frequency band | 850/900/1800/1900MHz |
| GPS sensitivity | -161 dB |
| Positioning accuracy | 2.5m |
| I/O port | 1 USB port |



TC68S Tracker

Quick Start Guide

CD download card

ACCESSORIES



OBD extension cord

Velcro

USB cable

Backup batter y (170 mAh/3.7 V)

C€ RoHS







+86(755)83462818



www.meitrack.com



info@meitrack.com



6/F, West Tower, Cafu Plaza (Sheraton Hotel), No. 5, Guihua Rd., Futian Free Trade Zone, Shenzhen, China. 518038